

LuxSpace G4 DN58x/DN59x

Miniaturized downlight with leading optical performance & great diversity

A new range with full configurations, combining light comfort and leading performance with luxury looking. The miniaturized form factor achieves best integration with architecture. It is also compatible with smart control and indoor positioning system.

Benefits

- Energy saving counting on high system efficacy
- Compactness - less cut out with higher lumen
- Excellent light quality for visual comfort

Features

- System efficiency up to 120 lm/W
- 125mm up to 2000lm, 150mm up to 2600lm
- 700 ~ 4300lm, BA60/30, DALI/POE

Applications

- Office
- Shopping mall
- Retail store
- Hotel



Dimensions & weight				
Model	Dia (mm)	H (mm)	W (kg)	Cut out (mm)
D100	112	68	0.38	100~105
D125	137	90	0.45	125~130
D150	162	100	0.80	150~155
D200	212	130	1.40	200~205

Technical specifications

CRI >80	SDCM <3.5	PF >0.9	IP20 IP54	220-240V 50/60Hz
---------	-----------	---------	-----------	------------------

Model	DN588/589/590/591/592/593/594B			
System lumen	740/1000/1500/2000/2600/3400/4300lm			
System power	PSU	6.6W/8.4~9.3W/13.5W/17.5~19.3W/22.6W/32.5W/39.7W		
	PSD	8W/10.5W/14W/18.8W/17.5~20W/23.3W/30.8W/39W		
Efficacy	110 ~ 120 lm/W			
LED driver	Fixed output /DALI/DALI-VLC (ETO)/ POE (To be released)			
Color temp.	3000K/4000K			
Materials & finishing	Reflector: Aluminum PC diffuser with high haze and light transmission Die-casting aluminum heat sink			
Lifetime	50,000 hours (70% lumen maintenance @ Ta = 25°C)			
Working temp.	- 20°C < Ta < 40°C			
Standards/ Certifications	CE, IEC60598 (CB scheme)			

* IP54: Front cover with glass only

Note: Product specifications can be changed without prior notice. More options are available on request. Please contact your local representatives.

