

SlimBalance G2 SP560P

Simplicity with elegance

A cost effective linear suspension office offer with multiple lumen outputs and sizes. Its sleek and elegant design helps create attractive and differentiated office spaces. Its max diffuser length reaches 12m which provides no diffuser gap between 2 luminaires for better visual comfort. PSU, Dali, Interact System are offered for easy and flexible light control.

Benefits

- Multiple lengths and widths to fit different office applications
- Max 12m continuous diffuser installation makes office visually better
- System options available to easily control the lights

Features

- Lengths options with 600/1200mm; width options with 30/60/90mm
- CRI 80 with flicker free
- Dali and Interact system available

Applications

- Open ceiling office
- Meeting room
- Reception area
- Corridor
- Circulation area



interact ready.

CRI 80 CRI 90	SDCM ≤4	PF 0.9	IP20 IP40	220-240V 50/60Hz
------------------	------------	-----------	--------------	---------------------

Technical specifications

Model	SP560P					
	W30mm		W60mm		W90mm	
Type	L600mm	L1200mm	L600mm	L1200mm	L600mm	L1200mm
System lumen	Max 1200lm	1200lm	2000lm	4000lm	2500lm	4000lm
System efficacy	95 ~ 100 lm/W		110 ~ 115 lm/W		110 ~ 115 lm/W	
System power	6W/12W		19W/20W/35W		12W/19W/20W/35W	
Color temp.	4000K/ 3000K, 6500K (ETO)					
LED driver	PSU/PSD for Wave I WIA/Tunable White for Wave II					
CRI	80/90 (ETO)					
Materials & finishing	Housing: Extru Aluminum					
Lifetime	50,000 hours (70% lumen maintenance @ Ta = 25°C)					
Working temp.	-20°C < Ta < 40°C					
IP rating	IP20 for continuous; IP40 for single installation					
Mounting	Suspended (Mounting accessories are not provided)					
Standards/Certifications	CCC/CB					

Note: Product specifications can be changed without prior notice.
More options are available on request. Please contact your local representatives.

