




GreenUp Round Highbay BY518P

Classic, economical and reliable Highbay

Providing the optimal balance between basic performance and price, the family covers a wide product range with a variety of options, competitive specifications, and long-term quality and reliability. The range is suitable for most industrial applications.

Benefits

-  Excellent energy savings
-  Great value for money
-  Robust and reliable

Features

- System efficacy up to 143 lm/W
- Narrow and wide beam options
- A wide range of lumen packages for different applications

Applications

- General manufacturing
- Warehouses
- Logistical centers



Technical specifications

CRI >80	SDCM 5	PF 0.95	Class I	IP65 IK06	220-240V 50/60Hz
---------	--------	---------	---------	-----------	------------------

Model	BY 518P PSU				
	LED 110	LED 160	LED 210	LED 260	LED 300
Lumen output	11000lm	16000lm	21000lm	26000lm	30000lm
System power	77W	115W	154W	187W	207W
System efficacy	143 lm/W	139 lm/W	137 lm/W	139 lm/W	143 lm/W
Color temp.	3000K/4000K/6500K				
Working temp.	-24°C to +45°C (Ta 35°C)				
Lifetime	50,000 hours (L70B50@35°C)				
Optics	WB/NB				
Surge protection	2KV/4KV				
Mounting	Suspension (Loop/Pipe); Surfaced (Bracket), (Loop default included in the box for GM version, NOT included in the box for GC version); Optional: Bracket				
Dimensions (DxH)	Ø278x89mm	Ø278x89mm	Ø305x99mm	Ø358x99mm	Ø416x99mm
Weight	1.9kg	1.9kg	2.3kg	3kg	3.7kg
Certifications	CCC/CB/EMC/CE				

Note: Product specifications can be changed without prior notice. More options are available on request. Please contact your local representatives.

