

# GreenPerform Highbay Elite BY718P

Elegant industrial design with fantastic light quality

A completely new finless aesthetics design which owns iF design award 2019 & Reddot design award 2019 and offers higher system efficiency, better light quality, longer lifetime and interact technology with affordable price.

## Benefits

- High energy saving – up to 71% comparing to HPI-P system
- Robust & reliable with a long service lifetime
- Slim design - easy for installation and maintenance

## Features

- Best in class with 75,000 hours (L70) lifetime
- Multi-sites lighting management with InterAct technology
- Elegant industrial design
- Superior light quality
- Various application requirements satisfied with complete product family

## Applications

- General manufacturing
- Warehouses & logistical centers
- Exhibition halls & high ceiling lounges



interact ready.



CRI >80	SDCM <5	PF 0.9	THD <15%	IP65 IK08	220-240V 50/60Hz
---------	---------	--------	----------	-----------	------------------

## Technical specifications

Model	BY718P				
	LED100	LED150	LED200	LED250	LED300
System lumen	10000lm	15000lm	20000lm	25000lm	30000lm
System power	PSU 68W	102W	135W	169W	203W
	PSD 73W	109W	145W	183W	217W
System efficacy	PSU: Typ. 145 lm/W; PSD: Typ. 137 lm/W				
Color temp.	6500K/4000K				
Working temp.	-30°C to +50°C (Ta35°C)				
Lifetime	75,000 hours (L70B50 @35°C)				
Optics	WB, NB				
Mounting	Hook (included); Optional: Pipe, Bracket				
Housing	Aluminum die-casting				
Diameter	Ø385mm	Ø415mm	Ø450mm	Ø510mm	
Height, weight	PSU 95mm, 3.3kg	90mm, 4.3kg	95mm, 4.7kg	90mm, 5.8kg	
	PSD 415mm, 6kg	445mm, 7kg	445mm, 7.7kg	464mm, 10kg	
Standards/ Certifications	CE, IEC60598 (CB scheme)				

Note: Product specifications can be changed without prior notice. More options are available on request. Please contact your local representatives.

