

GreenPerform Waterproof G3 WT198C

A high-performance, energy-efficient waterproof offering

A superb choice for hard-working applications. Not only does it provide excellent optical performance, it also delivers substantial energy saving. And because it works seamlessly with IoT software like Interact, it also offers the option of customization, convenience, and data-driven insights.

Benefits

- 👁️ Excellent light quality
- 🔧 Easy Installation
- 📶 Fully connected - DALI, InterAct ready

Features

- Superior optics - up to 140 lm/W, wide beam with glaring control
- Product diversity with 3 lengths, multiple lumen options
- Reliable performance with lifetime of 50,000 hours

Applications

- Production line and assembly line
- Warehouse
- Food industry
- Parking lot
- Public area



interact ready.

CRI >80	SDCM <5	PF 0.9	IP65 IK08	220-240V 50/60Hz
---------	---------	--------	-----------	------------------

Technical specifications

Model	WT198C L600	WT198C L1200	WT198C L1500		
System lumen	(WB) 1900lm (PCO) 1800lm	2700lm 2500lm	4000lm 3700lm	6000lm 5700lm	8000lm 7500lm
System power	15W	21W	29W	43W	57W
System efficacy	(WB) 127 lm/W (PCO) 121 lm/W	132 lm/W 122 lm/W	140 lm/W 128 lm/W	140 lm/W 130 lm/W	140 lm/W 133 lm/W
Fixed output	✓	✓	✓	✓	✓
DALI		✓	✓	✓	✓
InterAct Industry			✓	✓	
Color temp.	4000K/6500K (ETO)				
Optics	Opal cover for Lambertian, Prismatic cover for wide beam				
Dimensions (LxWxH)	665x80x76mm	1215x80x76mm	1515x80x76mm		
Working temp.	-25 to +40°C				
Lifetime	50,000 hours (L75B50 @Ta 25°C)				
Materials & finishing	Housing: PC/Optical cover: PC				
Mounting	Surfaced/Suspended				
Standards/ Certification	CE, IEC60598 (CB scheme)				

Note: Product specifications can be changed without prior notice. More options are available on request. Please contact your local representatives.

