

GreenUp Slim Downlight DN150

Ultra-thin for general lighting applications with limited build-in height

Suitable for a series of lighting applications in office, retail and general area lighting. Available in a wide variety of lumen packages, cut-out sizes, color temperatures and dimming options as ETO option.

Benefits

- Compact design for better integration with the building
- Comfortable light with high efficiency
- Connected lighting and future-proof smart technology

Features

- Recessed
- On/off (DALI, 1-10V ETO)
- Reliable performance for indoor applications

Applications

- Office
- Shopping mall
- Restaurant
- Hospitality



Dimensions	
Model	Cut out (mm)
DN150B LED6S	68~73
DN150B LED10S	127~132
DN150B LED15S	152~157
DN150B LED20S	203~208

CRI ≥80	SDCM 5	IP20 IP44	220-240V 50/60Hz
---------	--------	--------------	---------------------

Technical specifications

Model	DN150B LED6S	DN150B LED10S	DN150B LED15S	DN150B LED20S
Light source	Back light	Edge light	Edge light	Edge light
System lumen	650lm	1100lm	1500lm	2100lm
System power	6.5W	11W	15W	21W
Driver	Standard: PSU ETO: 1-10V	Standard: PSU ETO: 1-10V/DALI	Standard: PSU ETO: 1-10V	Standard: PSU ETO: 1-10V/DALI (cut-out 152~157mm)
Materials & finishing	Optical: PC diffuser		Optical: PS diffuser + PMMA LG + PET reflector Housing: Die-casting aluminum	
Color temp.	STD: 3000K/4000K; ETO: 6500K			
Lifetime	50,000 hours (L70 @Ta=25°C)			
Mounting	Recessed fixed by spring tension clips			
Working temp.	-20°C ~ 40°C			
Standards/Certifications	CE, IEC60598 (CB scheme)			

Note: Product specifications can be changed without prior notice.
More options are available on request. Please contact your local representatives.

