




SmartBright Suspension G2 RC095V

The most affordable LED solution for linear suspension

Designed specially for open ceilings where traditional installation cannot work. The complete product family offers a variety of dimensions with focus on suspension applications, covering wider potential applications.

Benefits

-  Stylish product look & feel
-  Excellent uniformity for light exit window
-  Flicker Free for good on site experience

Features

- System efficacy up to 93 lm/W
- Lumen output up to 3000 lm/1.2m
- Suspension mounting with multiple accessory options

Applications

- Open plan office
- Meeting room
- Circulation area



Suspension kit

Technical specifications

CRI ≥80	PF >0.9	SDCM ≤5	IP20 IK02	Class I	220-240V 50/60Hz
---------	---------	---------	-----------	---------	------------------

Model	L1200			L600	
Dimensions (LxWxHmm)	1200x120x50	1200x100x50	1200x70x50	600x120x50	600x70x50
System lumen	3000lm	2900lm	2600lm	1500lm	1300lm
System power	34W	32W	28W	16W	14W
System efficacy	88 ~ 93 lm/W				
Color temp.	4000K/6500K				
Working temp.	-10°C to +35°C				
Lifetime	25,000 hours (L70B50@25°C)				
LED driver	Fixed output				
Materials & finishing	Housing: SPCC; Diffuser: PC; Colors: White/Dark				
Mounting	Suspended with suspension kit (separate 12nc, 2pcs/set)				
Standards/Certifications	CB/CE				

Note: Product specifications can be changed without prior notice. More options are available on request. Please contact your local representatives.

